



**Job Site Speaker**  
DMR203 12V max-18V / AC

Satisfy Professional's Needs



# Powerful & Deep Stereo Sound

*Wireless Stereo Pairing*

Left

Right



 **Bluetooth®**

**12V<sub>max</sub>**  
LITHIUM-ION

**18V**  
LITHIUM-ION

# Multi-speaker connection

## True Wireless Stereo

True Wireless Stereo (TWS) technology allows to wirelessly pair two DMR203's via Bluetooth multi-pairing and to enjoy a deep, rich and powerful stereo sound.




## Group chain

Up to ten DMR203's can be paired and connected to one mobile device to play the same sound simultaneously.



## 7 Selectable sound modes

- Sound mode can be selected to suit the music genre.
- MY EQ (my equalizer) mode enables to individually adjust treble, midrange and bass for a desired sound quality.



### Equalizer

FLAT / JAZZ / ROCK / CLASSIC / POP / NEWS / MY EQ

Dust and water resistance (only with DC power)

# IP65

For use in outdoor applications or harsh environments



### Color LCD panel

- displays the status of speaker and equalizer settings.
- displays song titles and artist names, etc.



## 2 way high quality speaker

Woofer : Ø 101.6mm, for low sound  
Tweeter : Ø 36mm, for high sound



### Connection

Bluetooth



### AUX-IN jack



USB output terminal for charging smartphone etc.



Storage box for portable devices  
Mobile device can be charged while stored.



### Power source

Li-ion battery (slide type)

12Vmax

18V



AC



## Continuous run time (approx): hour

On a single full battery charge

12V max	Bluetooth		18V	Bluetooth	
	AUX IN			AUX IN	
BL1016 (1.5Ah)	8.5	9.5	BL1815N(1.5Ah)	7.5	8.5
			BL1820B(2.0Ah)	10	11
BL1021B (2.0Ah)	11	12	BL1830B(3.0Ah)	14	16
			BL1840B(4.0Ah)	20	22
BL1041B (4.0Ah)	22	25	BL1850B(5.0Ah)	26	29
			BL1860B(6.0Ah)	32	35

## Job Site Speaker

**DMR203** 12V max-18 V / AC

<b>Speaker Size</b>	Woofer/Tweeter: Ø101.6 / Ø36 mm
<b>Max Output</b>	18V / 12Vmax / AC : 10 / 3.5 / 3.5 W
<b>Bluetooth</b>	Version: 5.0 Profile: A2DP / SCMS-T / AVRCP Supported Codec: SBC Max Transmission Range (Optimum): 10 m (33 ft) Max Transmission Range (Possible): 30 m (100 ft)
<b>Dimensions (L x W x H)</b>	w/ Handle in Retracted Position: 217x206x199 mm (8-1/2"x8-1/8"x7-7/8") w/ Handle in Upright Position: 217x206x285 mm (8-1/2"x8-1/8"x11-1/4")
<b>Net weight</b>	2.7 - 3.4 kg (6.0 - 7.5 lbs.)

Standard Equipment : AC Adapter

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

# Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201912