



Job Site Radio
MR001G / MR002G
MR003G / MR004G
 12Vmax-40Vmax / AC

Satisfy Professional's Needs



**Newly Compatible
 with 40Vmax XGT
 Li-ion Batteries**



photo: MR002G



MR001G



MR002G



MR003G



MR004G

	dab+	Bluetooth®
MR001G	—	—
MR002G	—	✓
MR003G	✓	—
MR004G	✓	✓

Powered by AC or DC





MR002G / MR004G only
equipped with Bluetooth class 2** to wirelessly play music from a mobile device.
**With a range of 10m (33ft); up to 30m (100ft) in good radio conditions



MR003G / MR004G only

Dust and shower-proof construction: IP65
(when using battery)



Dual power sources

Runs on AC adapter or Makita rechargeable Li-ion batteries.



40V^{Li-ion}max
BL4020 / BL4025 / BL4040

18V^{Li-ion}max
BL1815N /
BL1820B /
BL1830B /
BL1840B /
BL1850B /
BL1860B

AC adapter jack

12V^{Li-ion}max
BL1016 / BL1021B / BL1041B

USB output port

MR002G / MR004G only
• Output: 2.4A
• Port quantity: 1



AUX-IN jack

used as a stereo speaker by connecting to external audio source with a commercial connecting cable.

Increased speaker size

89 mm x2



Carry handle with built in FM antenna

photo: MR002G

Continuous run time (approx): hour

On a single full battery charge
MR001G / MR002G / MR003G / MR004G

12V max	BL1016(1.5Ah)	8 / 7.5 / 9.5 / 8.5
	BL1021B(2.0Ah)	11 / 9.5 / 12.5 / 11
	BL1041B(4.0Ah)	19.5 / 18.5 / 23.5 / 21
18V	BL1815N(1.5Ah)	7.5 / 6.5 / 8.5 / 7.5
	BL1820B(2.0Ah)	10 / 9 / 11 / 10
	BL1830B(3.0Ah)	14 / 12.5 / 16 / 14
	BL1840B(4.0Ah)	20 / 17.5 / 22 / 20
	BL1850B(5.0Ah)	25.5 / 23 / 29 / 26
	BL1860B(6.0Ah)	31 / 27.5 / 34 / 31
40V max	BL4020(2.0Ah)	14.5 / 13.5 / 17 / 15
	BL4025(2.5Ah)	18.5 / 17 / 21 / 19
	BL4040(4.0Ah)	30 / 27.5 / 34 / 30

Job Site Radio

MR001G / MR002G / MR003G / MR004G 12Vmax-40Vmax / AC

Frequency Band	MR001G / MR002G: FM / AM: 87.5 - 108 MHz / 522 - 1,710 kHz MR003G / MR004G: FM / DAB / DAB+: 87.5 - 108 MHz / 174.928 - 239.200 MHz / 174.928 - 239.200 MHz
Speaker Size	Woofer: Dia. 89 mm x2
Max Output	MR001G / MR002G: 40Vmax: 5 W x2 MR003G / MR004G: 40Vmax: 4.9 W x2
Bluetooth	Version: 5.0
(MR002G / MR004G only)	Profile: A2DP / SCMS-T MR001G / MR002G: Supported Codec: SBC MR003G / MR004G: Supported Codec: SBC / AAC Max Transmission Range (Optimum): 10 m (33 ft) Max Transmission Range (Possible): 30 m (98 ft) Transmission Power Class: 2 Compatible Bluetooth Profile: A2DP
Dimensions (L x W x H)	w/ Handle in Upright Position: 280 x 171 x 434 mm (11 x 6-3/4 x 17-1/8")
Net weight	4.6 - 5.4 kg (10.1 - 11.9 lbs.)

Standard Equipment: AC Adaptor, AA Battery (MR001G / MR002G only)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202101