



Cordless Rear Handle Saw  
RS002G 260 mm (10-1/4")



**40V** **Li-ion**  
**max**



High power

**10" Rear Handle Saw**  
(260mm)

Cuts 4x material in a single pass  
with max cutting capacity 95 mm.

Lightweight  
(with BL4050F)

**6.3 kg**







## High power **BL MOTOR**

High power 40Vmax XGT Li-Ion battery and high efficiency BL motor provides easier and more comfortable cutting than corded rear handle saws.

### Connectable to vacuum cleaners



Connect a Makita vacuum cleaner to your tool.




### Wide hook

- Compatible with up to 66mm width
- The machine can be hung onto, for example, 2x lumbers or I-joint (with a width of 64mm), etc.



### Bevel angle up to 56 degrees

Knob and stopper for bevel adjustment with positive stops at 22.5 and 45 degrees.



### Auto-start Wireless System



**Electric brake system** enables you to start the next operation quickly.



### Using magnesium diecast

for Base Plate, Blade Case and Safety cover, tool weight has been reduced without loss of durability and power.

### Soft start



### eXtreme Protection Technology



## Cutting Performance

90x300mm Melapi cutting at 0 degrees, cross-cut

(with BL4050F)  
**80 cuts**

The test results depend to a great extent on the hardness of the test material, etc.

40Vmax series movie



40Vmax mechanism movie



This movie was filmed in Japan. Models and specs may vary by country.

### 40Vmax Sawing lineup

Rear Handle Saw RS001G

Circular Saw HS003G/HS004G



Slide Compound Miter Saw LS002G/LS003G

## Accessories

### Guide Rule (Rip fence)

Use with thumb screw M6x14 Part No. 265701-9

Part No. 165153-3



## Battery Charging Time Reference

	DC40RA (Fast Charge)	DC40RC
<b>BL4050F</b> *15.0Ah	50min	85min
<b>BL4040</b> 4.0Ah	45min	67min
<b>BL4025</b> 2.5Ah	28min	38min
<b>BL4020</b> 2.0Ah	22min	30min

\*1 Recommended battery

## Cordless Rear Handle Saw

### RS002G 260 mm (10-1/4")

Brake	<b>Blade Diameter</b> 260 mm (10-1/4")
Soft Start	<b>Max Cutting Capacity</b> 90°: 95 mm (3-3/4") 45°: 70 mm (2-3/4") 56°: 54.5 mm (2-1/8")
Dust Collecting	<b>No Load Speed (RPM)</b> 4,000
Carrying Case (country-specific)	<b>Vibration Level</b> 2.5m/s <sup>2</sup> or less
	<b>Sound Pressure Level</b> 96 dB(A)
	<b>Sound Power Level</b> 107dB(A)
	<b>Dimensions (L x W x H)</b> 489 x 193 x 309 mm (19-1/4 x 7-5/8 x 12-1/8")
	<b>Net weight</b> 5.7 - 6.3 kg (12.6 - 13.9 lbs.)

#### Standard Equipment:

TCT Saw Blade, Grip, Offset Wrench, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

# Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202101