



Electric Breaker
HM1511 / HM1501 1-3/16" : 30 mm Hex Shank
HM1512 / HM1502 1-1/8" : 28.6 mm Hex Shank

High power and Low vibration

photo: HM1511
Bit is option

Impact energy
[EPTA-Procedure 05/2009]

48.9 Joule

model: HM1511 / HM1512

Vibration Level
(at main handle)

6.5 m/s²

model: HM1511 / HM1512

AVT **SOFT**
NOLOAD
▲ HM1511 / HM1512 ▲

High power and Low vibration

Thanks to completely redesigned hammering mechanism and increased motor power as compared with predecessor model, higher power is achieved with minimum increase in tool size and weight.

AVT
ANTI VIBRATION TECHNOLOGY
(HM1511/ HM1512 only)

Active dynamic vibration absorber
(HM1511/ HM1512 only)

SOFT NO LOAD
(HM1511 / HM1512 only)
Suppression of motor speed during no-load



HM1511 / HM1501

HM1512 / HM1502

30mm Hex Shank

28.6mm Hex Shank



photo: HM1511



1 Power-ON indicator lamp
2 Service indicator lamp

Carrying case



Model	Shank	AVT	SOFT NO LOAD	Impact energy	Vibration
HM1511	30 mm Hex Shank	✓	✓	48.9 J	6.5 m/s ²
HM1501		—	—	48.1 J	14.5 m/s ²
HM1512	28.6 mm Hex Shank	✓	✓	48.5 J	6.5 m/s ²
HM1502		—	—	49.1 J	14.5 m/s ²

Accessories

Dust extractor attachment set

include vacuum hose
Part No. 191M20-4
Part No. 191M21-2



Electric Breaker

HM1511 / HM1501 1-3/16" : 30 mm Hex Shank

HM1512 / HM1502 1-1/8" : 28.6 mm Hex Shank

218

	HM1511 / HM1501	HM1512 / HM1502
Double Insulation	✓	✓
30mm Hex Shank HM1511 / HM1501		
28.6mm Hex Shank HM1512 / HM1502		
Soft Start	✓	✓
Carrying Case	✓	✓
	HM1511 / HM1501 1,850W EPTA-Procedure 05/2009: HM1511: 48.9 J / HM1501: 48.1 J 1,300 Blows Per Minute (BPM) Sound Pressure Level HM1511: 85 dB(A) / HM1501: 84 dB(A) HM1511: 105 dB(A) / HM1501: 104 dB(A) Sound Power Level Vibration Level HM1511: Chiselling Function w/ Side Handle: 6.5 m/s ² HM1501: Chiselling Function w/ Side Handle: 14.5 m/s ² 781 x 130 x 266 mm (30-3/4 x 5-1/8 x 10-1/2") Net weight HM1511: 19.2 kg (42.3 lbs.) / HM1501: 18.4 kg (40.6 lbs.) Power supply cord 5.0 m (16.4 ft)	HM1512 / HM1502 1,850W EPTA-Procedure 05/2009: HM1512: 48.9 J / HM1502: 49.1 J 1,300 Blows Per Minute (BPM) Sound Pressure Level HM1512: 84 dB(A) / HM1502: 85 dB(A) HM1512: 104 dB(A) / HM1502: 105 dB(A) Sound Power Level Vibration Level HM1512: Chiselling Function w/ Side Handle: 6.5 m/s ² HM1502: Chiselling Function w/ Side Handle: 14.5 m/s ² 809 x 130 x 266 mm (31-3/4 x 5-1/8 x 10-1/2") Net weight HM1512: 20.4 kg (45.0 lbs.) / HM1502: 19.7 kg (43.4 lbs.) Power supply cord 5.0 m (16.4 ft)
	<i>Standard Equipment</i> : Side Handle	

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.
Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202101