

Trakita Cordless Hedge Trimmer Series

Li-ion Max

Beyond cordless hedge trimmer

Optimum blade shape for smooth cutting of thin branches







5,000 min⁻¹





*Continuous run time on a single full battery charge/ No load continuous run time (approx)

40Vmax series movie

40Vmax mechanism movie



This movie was filmed in Japan. Models and specs may vary by country.

BL motor provide high power and excellent cutting performance



Li-ion Max





Anti-vibration structure consisting of Motor-crank section and handle section linked by cushions to absorb vibration from blade and motor-crank section



5 position rotating rear handle



Twigs are caught easily and held firmly Sharp edge curve Blade / Sharp edge Blade UH006G / UH007G UH004G / UH005G





NEW Chip receiver

can make it easier for user to collect leaf and twig debris, thanks to: - lower height of the connecting hooks

- reduced step height of the edge of the chip catching plate



Model	Shear blade assembly	Blade Cover	Chip receiver assembly set							
UH004G	191R53-9	412911-1	191R51-3							
UH005G	191R54-7	412912-9	191R52-1							
UH006G	191R55-5	412911-1	191R51-3							
UH007G	191R56-3	412912-9	191R52-1							
UH008G	191R57-1	459121-9	191R51-3							
UH009G	191R58-9	459122-7	191R52-1							

Accessories





Contact point is only both tips. Sharp edge blades: Upper blade...curveing downward Lower blade...curveing upward

Optimum blade shape for smooth cutting Sharp edge curve Blade UH004G / UH005G





3-speed Medium



eXtreme Protection Technology

Enhanced Dust and Drip-proof Performance ensure reliable operation even under bad weather



High water-resistance allows to operate the machine even if it is wet with water.

Charging Time Reference

40V max	DC40RA RetConging	DC40RC
*1 BL4020 2.0Ah	22min	30 _{min}
*1 BL4025 2.5Ah	28min	38 _{min}
*1 BL4040 4.0Ah	45 _{min}	67min
BL4050F 5.0Ah	50min	85min

*1 Recommended battery

Cordless Hedge Trimmer UH004G, UH005G, UH006G, UH007G, UH008G, UH009G

	UH004G	UH005G	UH006G	UH007G	UH008G	UH009G
Blade Length	600 mm (23-5/8")	750 mm (29-1/2")	600 mm (23-5/8")	750 mm (29-1/2")	600 mm (23-5/8")	750 mm (29-1/2")
Max Cutting Capacity	23.5 mm (15/16")	23.5 mm (15/16")	25.0 mm (1")	25.0 mm (1")	21.5 mm (7/8")	21.5 mm (7/8")
Strokes Per Minute	High / Mid / Low:	High / Mid / Low:	High / Mid / Low:	High / Mid / Low:	High / Mid / Low:	High / Mid / Low:
(SPM)	5,000/3,600/2,000	5,000/3,600/2,000	4,000/3,000/2,000	4,000/3,000/2,000	5,000/3,600/2,000	5,000/3,600/2,000
Sound Pressure Level	85 dB(A)	86 dB(A)	81 dB(A)	81 dB(A)	82 dB(A)	83 dB(A)
Sound Power Level	96 dB(A)	97 dB(A)	92 dB(A)	92 dB(A)	93 dB(A)	94 dB(A)
Vibration Level	Front / Rear:	Front / Rear:	Front / Rear:	Front / Rear:	Front / Rear:	Front / Rear:
	2.9 / 2.5 m/s ² or less	3.1/2.7		3.4/3.1		3.2/2.5
Dimensions	w/BL4020/BL4025:	w/BL4020/BL4025:	w/BL4020/BL4025:	w/ BL4020 / BL4025:	w/ BL4020 / BL4025:	w/BL4020/BL4025:
(L x W x H)	1,120 x 223 x 191 mm	1,263 x 223 x 191 mm	1,123 x 223 x 191 mm	1,274 x 223 x 191 mm	1,120 x 223 x 191 mm	1,262 x 223 x 191 mm
	(44 x 8-3/4 x 7-1/2")	(49-3/4 x 8-3/4 x 7-1/2")	(44-1/4 x 8-3/4 x 7-1/2")	(50-1/4 x 8-3/4 x 7-1/2")	(44 x 8-3/4 x 7-1/2")	(49-3/4 x 8-3/4x 7-1/2")
Net weight	4.3 - 4.9 kg (9.5 - 10.8 lbs.)	4.5 - 5.1 kg (9.9 - 11.2 lbs.)	4.4 - 5.0 kg (9.7 - 11.0 lbs.)	4.6 - 5.2 kg (10.1 - 11.5 lbs.)	4.3 - 4.9 kg (9.5 - 10.8 lbs.)	4.4 - 5.0 kg (9.7 - 11.0 lbs.)
	Max Cutting Capacity Strokes Per Minute (SPM) Sound Pressure Level Vibration Level Dimensions	Blade Length 600 mm (23-5/8") Max Cutting Capacity 23.5 mm (15/16") Strokes Per Minute High / Mid / Low: (SPM) 5,000 / 3,600 / 2,000 Sound Pressure Level 85 dB(A) Sound Power Level 96 dB(A) Vibration Level Front / Rear: 2.9 / 2.5 m/s ² or less Dimensions WiB4020 / BL4025: (L x W x H) (44 x 8-3/4 x 7-1/2")	Blade Length 600 mm (23-5/8") 750 mm (29-1/2") Max Cutting Capacity 23.5 mm (15/16") 23.5 mm (15/16") Strokes Per Minute High / Mid / Low: High / Mid / Low: (SPM) 5,000 / 3,600 / 2,000 5,000 / 3,600 / 2,000 Sound Pressure Level 85 dB(A) 86 dB(A) Sound Power Level 96 dB(A) 97 dB(A) Vibration Level Front / Rear: Front / Rear: 2.9 / 2.5 m/s ² or less 3.1 / 2.7 Dimensions w/ BL4020 / BL4025: w/ BL4020 / BL4025: (L x W x H) 1,120 x 223 x 191 mm 1,263 x 223 x 191 mm (44 x 8-3/4 x 7-1/2") (49-3/4 x 8-3/4 x 7-1/2")	Blade Length 600 mm (23-5/8") 750 mm (29-1/2") 600 mm (23-5/8") Max Cutting Capacity 23.5 mm (15/16") 23.5 mm (15/16") 25.0 mm (1") Strokes Per Minute High / Mid / Low: High / Mid / Low: High / Mid / Low: (SPM) 5,000 / 3,600 / 2,000 5,000 / 3,600 / 2,000 4,000 / 3,000 / 2,000 Sound Pressure Level 85 dB(A) 86 dB(A) 81 dB(A) Sound Power Level 96 dB(A) 97 dB(A) 92 dB(A) Vibration Level Front / Rear: Front / Rear: Front / Rear: 2.9 / 2.5 m/s ² or less 3.1 / 2.7 3.0 / 2.5 m/s ² or less Dimensions w/ BL4020 / BL4025: w/ BL4020 / BL4025: w/ BL4020 / BL4025: (L x W x H) 1,120 x 223 x 191 mm 1,263 x 223 x 191 mm 1,123 x 223 x 191 mm (44 x 8-3/4 x 7-1/2") (49-3/4 x 8-3/4 x 7-1/2") (44-1/4 x 8-3/4 x 7-1/2") (44-1/4 x 8-3/4 x 7-1/2")	Blade Length 600 mm (23-5/8") 750 mm (29-1/2") 600 mm (23-5/8") 750 mm (29-1/2") Max Cutting Capacity 23.5 mm (15/16") 23.5 mm (15/16") 25.0 mm (1") 25.0 mm (1") Strokes Per Minute High / Mid / Low: (SPM) 5,000/3,600/2,000 5,000/3,600/2,000 4,000/3,000/2,000 4,000/3,000/2,000 Sound Pressure Level 85 dB(A) 86 dB(A) 81 dB(A) 81 dB(A) Sound Power Level 96 dB(A) 97 dB(A) 92 dB(A) 92 dB(A) Vibration Level Front/Rear: Front/Rear: Front/Rear: Front/Rear: Dimensions w/BL4020/BL4025: w/BL4020/BL4025: w/BL4020/BL4025: w/BL4020/BL4025: (L x W x H) 1,120 x 223 x 191 mm 1,263 x 223 x 191 mm 1,274 x 223 x 191 mm 1,274 x 223 x 191 mm (44 x 8-3/4 x 7-1/2") (49-3/4 x 8-3/4 x 7-1/2") (44-1/4 x 8-3/4 x 7-1/2") (50-1/4 x 8-3/4 x 7-1/2")	Blade Length 600 mm (23-5/8") 750 mm (29-1/2") 600 mm (23-5/8") 750 mm (29-1/2") 600 mm (23-5/8") Max Cutting Capacity 23.5 mm (15/16") 23.5 mm (15/16") 25.0 mm (1") 25.0 mm (1") 21.5 mm (7/8") Strokes Per Minute High / Mid / Low: Sound Power Level 85 dB(A) 86 dB(A) 81 dB(A) 81 dB(A) 82 dB(A) 93 dB(A) Yibration Level Front / Rear: Front / Rear: Front / Rear: Front / Rear: Sound / 2.000 / 3.000 / 2.000 / 3.000 / 2.000 / 3.000 / 2.000 / 3.000 / 2.000 Sound / 3.000 / 2.000 / 3.000 / 2.000 Sound / 3.000 / 2.000 / 3.000 / 2.000 / 3.000 / 2.000 / 3.000 / 2.000 / 3.000 / 2.000 / 3.000 / 2.000 / 3.000 / 2.000 / 3.000 / 2.000 / 3.000 / 2.000 / 3.000 / 2.000 / 3.000 / 2.000 / 3.000 / 2.000 / 3.000 / 2.000 / 3.000 / 2.000 / 3.000 / 2.000 /

Standard Equipment : Blade Cover, Safety Goggles (country-specific), Chip Receiver, Battery, Charger

The weight does not include accessories but battery cartridge(s). The lightest and heaviest combination weight of the appliance and battery cartridge(s) are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan