

Satisfy Professional's Needs



Job Site Charger Radio
DMR300 / DMR301 12Vmax-18V / AC



Battery charging function



Capable of receiving



(DMR301 only)





Battery charging function

- Able to charge LXT/CXT batteries when powered by AC with AC adaptor
- Clear sound quality can be enjoyed even during battery charging.

Charging time: min

12Vmax			18V					
BL1016 (1.5Ah)	BL1021B (2.0Ah)	BL1041B (4.0Ah)	BL1815N (1.5Ah)	BL1820B (2.0Ah)	BL1830B (3.0Ah)	BL1840B (4.0Ah)	BL1850B (5.0Ah)	BL1860B (6.0Ah)
31	40	75	27	38	48	67	84	100



Charging status indication

- LCD screen indicates battery charging status; Charging, Charging completed, Standing-by for charging, charging error.
- It also indicates that the battery has reached 80% charge.



Indicator for battery capacity	Charging status
(blinking)	Charging (less than 80%)
(blinking)	Charging (80% or more has been charged)
(lights up)	Charged (100%)

Dust and shower-proof construction: IP64



For use in outdoor applications or harsh environments



equipped with Bluetooth class 2** to wirelessly play music from a mobile device.

**With a range of 10m (33ft); up to 30m (100ft) in good radio conditions



AUX-IN jack



used as a stereo speaker by connecting to external audio source with a commercial connecting cable.

USB output port



- allows for charging a mobile device.
- Type A USB socket for DC5V/ 2.4A USB output

Bottle opener



Capable of receiving



(DMR301 only)

Dual power sources

Runs on AC adapter or Makita rechargeable Li-ion batteries.



BL1815N / BL1820B / BL1830B / BL1840B / BL1850B / BL1860B



BL1016 / BL1021B / BL1041B

AC adapter jack

Continuous run time (approx): hour

On a single full battery charge

	BL1016 (1.5Ah) 6.3		BL1815N(1.5Ah) 6.1	BL1840B(4.0Ah) 16
12V max	BL1021B(2.0Ah) 8.2	18V	BL1820B(2.0Ah) 8.2	BL1850B(5.0Ah) 20.5
	BL1041B(4.0Ah) 16.4		BL1830B(3.0Ah) 11.3	BL1860B(6.0Ah) 24.7

Job Site Charger Radio

DMR300 / DMR301 12Vmax-18 V / AC

Frequency Band	DMR300: FM / AM: 87.5 - 108 MHz / 522 - 1,710 kHz DMR301: FM / DAB/DAB+: 87.5 - 108 MHz / 174.928 - 239.200 MHz
Speaker Size	Woofer: Ø89 mm x2
Bluetooth	Version: 5.0 Profile: A2DP / SCMS-T Supported Code: SBC Max Transmission Range (Optimum): 10 m (33 ft) Max Transmission Range (Possible): 30 m (98 ft) Transmission Power Class: 2
Dimensions (L x W x H)	w/ Handle in Retracted Position: 268x185x305 mm (10-1/2"x7-1/4"x12") w/ Handle in Upright Position: 268x185x427 mm (10-1/2"x7-1/4"x16-3/4")
Net weight	5.9 - 6.6 kg (13.0 - 14.6 lbs.)

Standard Equipment :AC Adaptor, AA Battery

The weight may differ depending on the attachment(s), including the battery cartridge.
Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202102