

Cordless Finishing Sander DBO380 / DBO381

Stress-free sanding without cord







Continuous run time

about 50 min Battery: BL1860B (on a full battery charge)









Powered by 18V LXT Li-Ion battery

Both motor and battery are located above the sanding face to suppress fluttering of the base, enabling to provide an evenly finished surface.

BL motor

the same or higher work efficiency than predecessor model for sanding wood





3-stage electric speed control: 4,000/ 8,000/



12,000min⁻¹





Also connectable to Makita vacuum cleane







ensures easy installation/removal of paper with rolled clamper's edges.

Independently replaceable Pad

sponge sleeve

it can be independently replaced as it isfastened to machine's base with screws. And surely saves your repairing cost.

Detachable front grip

Detachable without tools and can be ground close-to-wall





Battery protector

Prevents damage to the battery and work material



makita

Rigid aluminum foot with

provides high durability and effective vibration-absorbing performance.



connects to compatible vacuum cleaners via Bluetooth.





DBO381 only

Wireless unit



Battery protector

Part No. 422807-8









Dust box assembly

with Filter set (Nonwoven fabric) Part No. 135327-0



Filter set (*w/o mark of origin)

Nonwoven fabric

Part No. 195134-3 Part No. *195133-5



Part No. 140115-2



Punch plate

For conventional type of abrasive paper without pre-punched holes Part No. 194947-9



Pad complete

For use with Abrasive paperer or clamping type paper Part No. 194929-1

For use with Hook & loop type paper Part No. 194930-6



Charging Time

18V LITHUMHON	DC18RC DC18RD	DC18SD
BL1815N 1.5Ah	15 min	30 min
BL1820B 2.0Ah	24 _{min}	45 min
BL1830B 3.0Ah	22 min	60 min
BL1840B 4.0Ah	36 _{min}	90 min
BL1850B 5.0Ah	45 min	110 min
BL1860B 6.0Ah	55 min	130 min

Cordless Finishing Sander

DBO380 / DBO381

Electronic 3-Speed Constant speed control Dust Collection Carrying Case

Pad Size Abrasive Paper Size Orbits Per Minute (OPM) Strokes Per Minute (SPM) Orbit Diameter Vibration Level Sound Pressure Level

72 dR(A) Dimensions (L x W x H)

93 x 185 mm (3-5/8 x 7-1/4") 93 x 228 mm (3-5/8 x 9" 4,000 / 8,000 / 12,000 8,000 / 16,000 / 24,0000 ø2.0 mm(1/16") 3.6m/s²

w/BL1815N / BL1820B: 336x93x158 mm (13-1/4"x3-5/8"x6-1/4") w/BL1830B/BL1840B/BL1850B/BL1860B: 336x93x169 mm (13-1/4"x3-5/8"x(6-5/8") 1.9 - 2.2 kg (4.2 - 4.9 lbs.)

Net weight Standard Equipment:

Dust bag or Dust box, Punch plate, Battery protector (Country-specific), Abrasive paper 93-120, Wireless unit (Country-specific, DBO381 only), Wireless unit adapter(Country-specific, DBO381 only), Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan