



Adapter for USB ADP001G




40V Li-ION max

Charge your smart phones anytime, anywhere



Max USB output current: 2.4A

USB output switch



- Push button type ON-OFF switch enables on/off control of USB output. (LED indicator is on in green while the switch is on.)
- With auto-off function

Two USB output ports



ADP001G is equipped with two Type A USB ports for DC5V / 2.4A output from each port.

Strap hole



Number of times iPhoneXR can be recharged on a single full battery charge





BL4020 (2.0Ah): 2.8
BL4025 (2.5Ah): 3.5
BL4040 (4.0Ah): 5.6
BL4050F (5.0Ah): 7.0



Not covered by EPTA-Procedure.

Items of standard equipment and specifications may vary by country or area.

Charging Time Reference

	DC40RA Fast Charging	DC40RC
 BL4020 2.0Ah	22min	30min
 BL4025 2.5Ah	28min	38min
 BL4040 4.0Ah	45min	67min
 BL4050F 5.0Ah	50min	85min

Adapter for USB

ADP001G

Smart phone charging	w/ BL4020 / BL4025 / BL4040 / BL4050F: 2.8 / 3.5 / 5.6 / 7.0
USB port	2 (A type)
Max USB output current	one port: 2.4 two ports: 4.8
Dimensions (L x W x H)	w/o Battery: 96 x 76 x 40 mm (3-3/4 x 3 x 1-9/16") w/ BL4020 / BL4025: 119 x 79 x 88 mm (4-11/16 x 3-1/8 x 3-1/2")
Net weight	w/o Battery: 0.14 kg (0.3 lbs.) 0.8 - 1.4 kg (1.8 - 3.1 lbs.)

Item except ADP001G are sold separately.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202103