



# Cordless Angle Grinder X-LOCK series



# XGT 40V LI-ION max

## Just One Click

# X-LOCK



Quick and Effortless Wheel Change System



Slide Switch with Electric brake, AWS and Variable speed control by dial

- GA039G** 100mm
- GA040G** 115mm
- GA041G** 125mm



Paddle Switch with Electric brake, AWS and Variable speed control by dial

- GA042G** 100mm
- GA043G** 115mm
- GA044G** 125mm



Paddle Switch with Electric brake

- GA045G** 100mm
- GA046G** 115mm
- GA047G** 125mm




**BL  
 MOTOR**

High operating efficiency



**AFT** Active Feedback sensing Technology

Shuts down the tool, if the rotation speed suddenly slows down.



**X-LOCK**

Quick and Effortless Wheel Change System



Just one click to attach the accessories  
 easy removal just simply pull the lever



**AWS** Auto-start Wireless System

connects to compatible vacuum cleaner with Bluetooth.  
 The vacuum cleaner automatically runs while the switch is on.



Wireless unit

GA039G, GA040G, GA041G  
 GA042G, GA043G, GA044G only

Vacuum cleaner is activated

Switch on the tool



Toolless wheel cover (Slide lever style)

allows for fast and easy angle adjustment and installation / removal of wheel cover.



No over-tightening

X-LOCK accessories are firmly attached and cannot be mounted incorrectly.





### Variable speed control dial (3,000 - 8,500 RPM)

Matches the speed to your application.



GA039G, GA040G, GA041G, GA042G, GA043G, GA044G only

	No load speed (RPM)	Cutting / Rough grinding	Grinding / Finish grinding	Rust removal / Paint removal	Stainless steel polishing
1	3,000				✓
2	4,500			✓	✓
3	6,000		✓	✓	✓
4	7,500		✓		
5	8,500	✓			

### No downtime

of installing and removing the accessories. Improve your work efficiency and work environment



### No tool required

X-LOCK mechanism ensures that the accessory is properly mounted to the tool even without nut, flange, and spanner.



### No scratching workpiece

by nuts even when flat grinding.



### Constant speed control

minimizes the reduction in wheel speed to provide stable grinding.



### Electric brake

maximizes productivity and increases safety for operator



### Extreme Protection Technology

is engineered for improved dust and water resistance



## Accessories

### Dust Collection wheel guard

for Diamond wheel  
GA041G, GA044G,  
GA047G only  
Part No.  
191G05-4



### Wheel cover

for abrasive cut-off wheel

Size	Part No.
100mm	162706-9
115mm	162707-7
125mm	162708-5



### Cutting W.C.A set for abrasive cut-off wheel

Size	Part No.
100mm	191V54-1
115mm	199709-0
125mm	199710-5



### Anti-vibration grip

Part No.  
194514-0



## Charging Time

	Fast Charging	
	DC40RA	DC40RC
BL4020 2.0Ah	22 min	30 min
*1 BL4025 2.5Ah	28 min	38 min
*1 BL4040 4.0Ah	45 min	67 min
*1 BL4050F 5.0Ah	50 min	85 min
BL4080F 8.0Ah	76 min	170 min

\*1 Recommended battery



## X-LOCK wheels

### Grinding wheel / Metal

Size	Part No.
100mm	E-00480
115mm	E-00365
125mm	E-00393



### Grinding wheel / Stainless

Size	Part No.
100mm	E-00496
115mm	E-00371
125mm	E-00402



### Thin Cut-off wheel / Stainless (Flat)

Size	Part No.
100mm	E-00505
115mm	E-00387
125mm	E-00418



### Diamond wheel / Concrete

Size	Part No.
100mm	E-02054
115mm	E-02060
125mm	E-02076



## Slide Switch Type

BL AWS AFT X-LOCK XPT

	GA039G	GA040G	GA041G
Wheel Diameter	100 mm (4")	115 mm (4-1/2")	125 mm (5")
Thread	X-Lock	X-Lock	X-Lock
No Load Speed (RPM)	3,000 - 8,500	3,000 - 8,500	3,000 - 8,500
Vibration Level	3.0 m/s <sup>2</sup>	3.4 m/s <sup>2</sup>	4.2 m/s <sup>2</sup>
Surface Grinding w/ Normal Side Grip:	2.5 m/s <sup>2</sup> or less	2.5 m/s <sup>2</sup> or less	2.5 m/s <sup>2</sup>
Disc Sanding w/ Normal Side Grip:	79 dB(A)	80 dB(A)	80 dB(A)
Sound Pressure Level / Sound Power Level	421 x 117 x 149 mm (16-1/2 x 4-5/8 x 5-7/8")	421 x 130 x 151 mm (16-1/2 x 5-1/8 x 5-15/16")	421 x 140 x 151 mm (16-1/2 x 5-1/2 x 5-15/16")
Dimensions (L x W x H) with/ BL4025:	459 x 117 x 178 mm (18 x 4-5/8 x 7")	459 x 130 x 180 mm (18 x 5-1/8 x 7-1/8")	459 x 140 x 180 mm (18 x 5-1/2 x 7-1/8")
with/ BL4050F:	3.0 - 5.3 kg (6.6 - 11.7 lbs.)	3.0 - 5.3 kg (6.6 - 11.7 lbs.)	3.0 - 5.3 kg (6.6 - 11.7 lbs.)
Net weight			

Variable Speed Brake Constant speed Soft Start Dust Collection Carrying Case

Standard equipment : Depressed Center Wheel, Cutting wheel cover attachment, Toolless Wheel Cover, Side grip, Battery, Charger

## Paddle Switch Type

BL AWS AFT X-LOCK XPT

	GA042G	GA043G	GA044G
Wheel Diameter	100 mm (4")	115 mm (4-1/2")	125 mm (5")
Thread	X-Lock	X-Lock	X-Lock
No Load Speed (RPM)	3,000 - 8,500	3,000 - 8,500	3,000 - 8,500
Vibration Level	3.3 m/s <sup>2</sup>	3.7 m/s <sup>2</sup>	4.5 m/s <sup>2</sup>
Surface Grinding w/ Normal Side Grip:	2.5 m/s <sup>2</sup> or less	2.5 m/s <sup>2</sup> or less	2.5 m/s <sup>2</sup> or less
Disc Sanding w/ Normal Side Grip:	81 dB(A) / 92 dB(A)	81 dB(A) / 92 dB(A)	81 dB(A) / 92 dB(A)
Sound Pressure Level / Sound Power Level	421 x 117 x 149 mm (16-1/2 x 4-5/8 x 5-7/8")	421 x 130 x 151 mm (16-1/2 x 5-1/8 x 5-15/16")	421 x 140 x 151 mm (16-1/2 x 5-1/2 x 5-15/16")
Dimensions (L x W x H) with/ BL4025:	459 x 117 x 178 mm (18 x 4-5/8 x 7")	459 x 130 x 180 mm (18 x 5-1/8 x 7-1/8")	459 x 140 x 180 mm (18 x 5-1/2 x 7-1/8")
with/ BL4050F:	3.0 - 5.4 kg (6.6 - 11.9 lbs.)	3.0 - 5.4 kg (6.6 - 11.9 lbs.)	3.0 - 5.4 kg (6.6 - 11.9 lbs.)
Net weight			

BL AFT X-LOCK XPT

	GA045G	GA046G	GA047G
Wheel Diameter	100 mm (4")	115 mm (4-1/2")	125 mm (5")
Thread	X-Lock	X-Lock	X-Lock
No Load Speed (RPM)	8,500	8,500	8,500
Vibration Level	3.3 m/s <sup>2</sup>	3.7 m/s <sup>2</sup>	4.5 m/s <sup>2</sup>
Surface Grinding w/ Normal Side Grip:	2.5 m/s <sup>2</sup> or less	2.5 m/s <sup>2</sup> or less	2.5 m/s <sup>2</sup> or less
Disc Sanding w/ Normal Side Grip:	81 dB(A) / 92 dB(A)	81 dB(A) / 92 dB(A)	81 dB(A) / 92 dB(A)
Sound Pressure Level / Sound Power Level	406 x 117 x 149 mm (16 x 4-5/8 x 5-7/8")	406 x 130 x 151 mm (16 x 5-1/8 x 5-15/16")	406 x 140 x 151 mm (16 x 5-1/2 x 5-15/16")
Dimensions (L x W x H) with/ BL4025:	444 x 117 x 178 mm (17-1/2 x 4-5/8 x 7")	444 x 130 x 180 mm (17-1/2 x 5-1/8 x 7-1/8")	444 x 140 x 180 mm (17-1/2 x 5-1/2 x 7-1/8")
with/ BL4050F:	2.9 - 5.3 kg (6.4 - 11.7 lbs.)	3.0 - 5.3 kg (6.6 - 11.7 lbs.)	3.0 - 5.3 kg (6.6 - 11.7 lbs.)
Net weight			

Variable Speed Brake Constant speed Soft Start Dust Collection Carrying Case

▲ GA042G, GA043G, GA044G

Standard equipment : Depressed Center Wheel, Cutting wheel cover attachment, Toolless Wheel Cover, Side grip, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area.

# Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202205