



Cordless Worklight ML005G 40Vmax / 18V



XGT
40V Li-ION
max

18V
LITHIUM-ION

Max luminous flux
3,600 lm



Continuous run time (approx)
on a full battery charge

High / Medium / Low

3.5 / 7.5 / 15 h

Battery: BL4040

Powered by:

- 40Vmax XGT Li-Ion battery
- 18V LXT Li-Ion battery



Max luminous flux
3,600 lm




3 brightness settings

with memory function that remembers the brightness setting last time you power off.



Switch



Front: about **6 m**
Side: about **6.4 m**



Distance

Battery capacity warning function



Automatically notifies the user about a decrease in battery capacity with a reduction in illuminance.

Carrying handle



Compact design with a short height thanks to the retractable carrying handle

Angle adjustment



Knob for free adjustment of light angle enables the light source to rotate from -30° to 210° to a desired angle.

Dust and water resistance
(only with DC power)

IP65

For use in outdoor applications or harsh environments

Accessories

Lamp shade

Part No. GM00002358

- provides widespread illumination and reduces the glare of LED light.
- reduces multiple shadows.



Anti-glare film

Part No. GM00002359

reduces glare.



Light stand

Part No. GM00002073



Charging Time

	Fast Charging			Fast Charging	
	DC40RA	DC40RC		DC18RC	DC18SD
*1 BL4020 2.0Ah	22 min	30 min	BL1815N 1.5Ah	15 min	30 min
*1 BL4025 2.5Ah	28 min	38 min	BL1820B 2.0Ah	24 min	45 min
*1 BL4040 4.0Ah	45 min	67 min	BL1830B 3.0Ah	22 min	60 min
*1 BL4050F 5.0Ah	50 min	85 min	BL1840B 4.0Ah	36 min	90 min
*1 BL4080F 8.0Ah	76 min	170 min	BL1850B 5.0Ah	45 min	110 min
			BL1860B 6.0Ah	55 min	130 min

*1 Recommended battery

The weight does not include battery cartridge

Items of standard equipment and specifications may vary by country or area.

Cordless Worklight

ML005G

Illuminance (High / Mid / Low)	at 1m from the light source : 2,100 / 1,000 / 500 lx
Luminous Flux	High / Mid / Low: 3,600 / 1,800 / 900 lm
Continuous illumination	High / Mid / Low: 3.5 / 7.5 / 15 h
Dimensions (L x W x H)	w/ Handle in Retracted Position : 248 x 309 x 296 mm (9-3/4 x 12-1/8 x 11-5/8") w/ Handle in Upright Position : 248 x 309 x 423 mm (9-3/4 x 12-1/8 x 16-5/8")
Net weight	4.6 - 6.5 kg (10.1 - 14.3 lbs.)

Standard Equipment : Anti-glare film

Battery & Charger Sold Separately

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202205