



Cordless Impact Driver TD003G



40V Li-ion max

Max fastening
torque

210
N·m



Work amount on a full battery charge BL4025

approx **280** pcs.

Drove 120mm coarse thread screws into melapi.



ved by
bit.



Max fastening torque
210
N·m

One LED job light each on both sides

Light mode

- To turn on the light, set F/R change lever in the neutral position, then pull the switch trigger. To turn off the light, pull the switch trigger again.
- The light turns off automatically one hour after turned on.



Constant speed control

Allows to operate the tool at the same speed as that at which you operate the tool on a full charged battery, even when the remaining battery capacity becomes low.

Variable speed control by trigger



eXtreme Protection Technology





BL
MOTOR

Aluminum hammer case

One-touch bit installation

Smoother installation of the bit has been achieved, reducing the resistance against insertion of the bit.

Anti-bit wobbling structure



Simple impact power selection

Mode	Rotation direction	Assist function
4 modes (for bolt)	Forward	Stops the machine approx 0.2 seconds after it has stopped impact blows.
	Reverse	No
T-mode (for thin metal only)	Forward	Stops the machine at the same time as impact blow is detected.
	Reverse	No




4 modes

(Max/ Hard/ Med. / Soft for bolt)

1 T-mode

(for thin metal only)

High Power
Durability
Digital
Communication



Accessories

Tool hanger set

Part No. 191F58-7

Enables to hook the machine quickly on a snap hook of waist belt, to prevent the machine from falling.



Charging Time

	Fast Charging	
	DC40RA	DC40RC
*1 BL4020 2.0Ah	22 min	30 min
*1 BL4025 2.5Ah	28 min	38 min
*1 BL4040 4.0Ah	45 min	67 min
BL4050F 5.0Ah	50 min	85 min
BL4080F 8.0Ah	76 min	170 min

*1 Recommended battery

Cordless Impact Driver

TD003G

- Variable Speed
- Brake
- Reversing
- Electronic 4-Speed
- Constant Speed
- Built-in Job Light
- Carrying Case

Capacity	Machine screw: M4 - M8 (5/32 - 5/16"), Standard bolt: M5 - M16 (3/16 - 5/8") High strength bolt: M5 - M14 (3/16 - 9/16"), Steel: 22 mm (7/8") Coarse thread (in length): 22 - 125 mm (7/8 - 4-7/8")
No Load Speed (RPM)	Max / Hard / Med. / Soft / T mode: 0 - 3,700 / 0 - 3,200 / 0 - 2,100 / 0 - 1,100 / 0 - 2,400
Impacts per minute (IPM)	Max / Hard / Med. / Soft: 0 - 4,100 / 0 - 3,600 / 0 - 2,600 / 0 - 1,400
Fastening torque	Hard / Med. / Soft: 170 / 50 / 20 N·m (1,510 / 440 / 180 in.lbs.)
Max fastening torque	210 N·m (1,860 in.lbs.)
Vibration Level	Impact tightening of fasteners of the maximum capacity of the tool: 11.9 m/s ²
Sound Pressure Level	95 dB(A)
Sound Power Level	106 dB(A)
Dimensions (L x W x H)	w/o Battery: 121 x 86 x 195 mm (4-3/4 x 3-3/8 x 7-5/8") w/ BL4020 / BL4025: 121 x 86 x 245 mm (4-3/4 x 3-3/8 x 9-5/8") w/ BL4040: 121 x 86 x 252 mm (4-3/4 x 3-3/8 x 9-7/8")
Net weight	1.7 - 2.9 kg (3.7 - 6.4 lbs.)

Standard Equipment : Belt clip, Hand strap (country-specific), Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202301