



Trimmer / Router series

with Anti-Restart Function and Soft Start series



3711

RP111C

RP2303FC

RT0702C

with Anti-Restart Function and Soft Start series

Trimmer



Router (Plunge type)



Product Comparison List

	Model No.	Continuous rating Input (W)	No load speed (rpm)	Switch	Variable Speed by dial	Constant Speed	Anti-restart function	Soft Start	Brake	Built-in Job Light	Dust Collecting
Trimmer	3711 (Standard base)	530	32,000	Toggle switch			●	●			
	3712 (Tilt base)	530	32,000	Toggle switch			●	●			
	RT0702C (4 different base)	710	10,000-30,000	Rocker switch	●	●	●	●			●
Router (Plunge type)	RP1111C	1,100	8,000 - 27,500	Trigger switch	●	●	●	●			●
	RP1802	1,850	23,000	Trigger switch			●	●			●
	RP1802F	1,850	23,000	Trigger switch			●	●			●
	RP1803	1,650	22,000	Trigger switch			●	●	●		●
	RP1803F	1,650	23,000	Trigger switch			●	●	●	●	●
	RP2302FC	2,300	9,000-23,000	Trigger switch	●	●	●	●	●	●	●
	RP2303FC	2,100	9,000-23,000	Trigger switch	●	●	●	●	●	●	●

Trimmer	3711/3712 6mm (1/4")	RT0702C 6mm (1/4"), 8mm (3/8")
	3711	3712
Double Insulation	530W	530W
Variable Speed (RT0702C)	6 mm or 1/4"	6 mm or 1/4"
Constant Speed (RT0702C)	32,000	32,000
Soft Start	94 dB(A)	94 dB(A)
Dust Collecting (RT0702C)	83 dB(A)	83 dB(A)
Carrying Case (RT0702C, 3712)	83 dB(A)	83 dB(A)
	RT0702C	
	710W	710W
	6 mm, 8mm or 1/4", 3/8"	6 mm, 8mm or 1/4", 3/8"
	10,000-34,000	10,000-34,000
	93 dB(A)	93 dB(A)
	82 dB(A)	82 dB(A)
	89 x 89 x 210 mm (3-1/2 x 3-1/2 x 8-1/4")	89 x 89 x 210 mm (3-1/2 x 3-1/2 x 8-1/4")
	1.8 - 2.8 kg (4.0 - 6.2 lbs.)	1.8 - 2.8 kg (4.0 - 6.2 lbs.)
	2.5m (8.2ft)	2.5m (8.2ft)
	Standard Equipment: 3711/ 3712: Collet Cone, Trimmer Guide, Straight Guide Assembly, Templet Guide, Straight Bit, Chip Deflector, Wrench x2 RT0702C: Collet Cone, Trimmer Base Assembly, Straight Guide Assembly, Templet Guide, Wrench x2, (country-specific: Dust Nozzle, Tilt Base Assembly, Plunge Base Assembly, Offset Base Assembly)	

Router	RP1111C 8mm (1/4")	RP1802/ RP1802F/ RP1803/ RP1803F/ RP2302FC / RP2303FC 12mm (1/2")
	RP1111C	RP1802/ RP1802F/ RP1803/ RP1803F
Double Insulation	1,100W	1,850W/ 1,850W/ 1,650W/ 1,650W
Variable Speed (RP1111C/ RP2302FC/ RP2303FC)	6mm, 8mm, or 1/4"	12mm or 1/2"
Constant Speed (RP1111C/ RP2302FC/ RP2303FC)	0 - 57mm (0 - 2-1/4")	0 - 70mm (0 - 2-3/4")
Soft Start	170 mm (6-11/16")	170 mm (6-11/16")
Electric Brake (RP1803/ RP1803F/ RP2303FC)	8,000 - 27,500	23,000/ 23,000/ 22,000/ 22,000
Built-in Job Light (RP1802F/ RP1803F/ RP2302FC/ RP2303FC)	104 dB(A)	96 dB(A)
Dust Collecting	93 dB(A)	85 dB(A)
	4.4 m/s ²	5.1 m/s ²
	110 x 269 x 260 mm	155 x 294 x 312mm
	(4-5/16 x 10-5/8 x 10-1/4")	(6-1/8" x 11-5/8" x 12-1/4")
	3.3kg (7.3lbs)	6.2kg (13.7lbs)
	4.0 m (13.1 ft)	4.0 m (13.1 ft)
	Standard Equipment: RP1111C: Straight guide, Collet cone, Nozzle assembly, Dust nozzle assembly, Trimmer guide, Wrench x2 RP1802/ RP1802F/ RP1803/ RP1803F/ RP2302FC / RP2303FC: Collet sleeve, Collet cone, Wrench x2, + Pan head screw M6x135 (Country-specific: Straight guide & Guide holder or Fine adjusting straight guide, Dust nozzle assembly, Knob 55 complete, Trimmer guide, Straight bit, Templet guide)	

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.
Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202111