

Trakita Cordless High Pressure Washer HW001G









Thakita.



tion mode can be selected to suit of the object to be cleaned.





IPX5

rated for weather and water resistance

High power brushless motor



Telescopic handle

for easy transportation and storage





Self-priming function

- Water can be supplied not only from faucet but also from water reservoirs, such as poly tanks, large buckets, using this function.
- Max suction height: 1m
- Minimal water level: 15mm
- No need to operate air drain valve

Accessory storage

Side section: Trigger gun Rear section: High pressure hose, Foam nozzle, Lance





NEW Foam nozzle set

New foam nozzle with improved foaming performance

Bottle capacity: 350mL









Two in parallel or one

Good mobility and transportability

makita

Large diameter wheels

Equipped with ø140mm wheels, allowing for good mobility even on bumpy road surfaces.

0



3 operation modes; opera the contamination degree

Max permissible pressure 115 MPa

3 operation modes

Mode With Vario- spray nozzle	Mode 3	Mode 2	Mode 1
Regular pressure	8.5Mpa	5.5Mpa	3.0Mpa
Regular flow rate	5.5L/min	4.2L/min	3.0L/min
Continuous use*	18min	30min	60min
Examples of recommended work	Washing of building exterior, etc.	Washing of vehicles, farm equip- ment, etc.	Light wash- ing work

* (approx) on fully charged batteries (with two BL4050F batteries)







Various options



Charging Time

40 V

BL4020 2.0Ah

BL4025 2.5Ah

BL4040/F 4.0Ah

*1**BL4050F** 5.0Ah

*1**BL4080F** 8.0Ah

*1 Recommended battery

st Charging

DC40RA

22 min

28 min

45 min

50 min

76 min

DC40RC

FA.

30 min

38 min

67 min

85 min

170 min

Cordless High Pressure Washer HW001G

Blectronic 3-Speed

Anti-restart function

Standard Equipment :

Trigger gun set, High pressure hose 5 m, Strainer assembly set, Absorption connector G3/4, Cleaner pin, Variospray nozzle set*1, Extension*1, Variospray lance set*1, Cyclone jet nozzle set*1, Variable nozzle set*1, Foam nozzle set*1, Wash brush set (Vertical form)*1, Hose assembly set*1, Hose clamp*1, Battery, Charger *1 Country specific

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according are shown in the table. Items of standard equipment and specifications may vary by country or area.

Max. Flow Rate Regular Flow Rate Max Permissible Pressure Regular Pressure Max Feed Temperature Max Suction Height Max Run Time

Hose Length Noise level Dimensions (L x W x H) Net weight 7.0 L/min Mode 1/2/3: 3.0/4.2/5.5 L/min 11.5 MPa Mode 1/2/3: 3.0/5.5/8.5 MPa 40 °C 1 m w/BL4050F x2: Mode 1/2/3: 60/30/18 min 5 m 84 dB(A) 334 x 383 x 520mm (13-1/2 x 15-1/8 x 20-1/2") 10.3 - 13.4 kg (22.7 - 29.5 lbs.)

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan