



Cordless Area Worklight ML010G 40Vmax, 18V, 14.4V / AC



40V L⁺ION max

18V LITHIUM-ION

Improved Self-righting performance



Up to 4 batteries can be installed in parallel.

two LXT batteries + two XGT batteries



Continuous run time (approx)

Low mode **59 hours**

Battery: BL4080F x2 & BL1860B x2
all LEDs light up



Max luminous flux

5,500 lm



Compatible with 3 power sources



3 brightness settings

with memory function of the setting last time you power off



Lighting area selection



Continuous run time (approx)

all LEDs light up

Battery	High	Medium	Low
BL1860B x2	4.5 h	8.5 h	16 h
BL4040 x2	6.5 h	11 h	21 h
BL4050F x2	8.5 h	14 h	27 h
BL4040 x2 + BL1860B x2	11 h	19.5 h	37 h
BL4050F x2 + BL1860B x2	13 h	22.5 h	43 h
BL4080F x2	13 h	23 h	43 h
BL4080F x2 + BL1860B x2	17.5 h	-	59 h

Battery capacity warning function



Hook for power cord



Battery fuel gauge



Padlock hole anti-battery theft



AC outlet allows for connecting up to 8 units of this light together.



IP54-rated water resistance (Only with DC power supply)



Diffusing lens
Daylight white (approx 5,500K)

Carrying handle



Reflector
glows in the dark to help you locate the worklight body.

Charging Time

	18V LITHIUMmax			40V ^{max} L ^{ITHIUM} max			
	DC18RC	DC18RD	DC18SD	DC40RA	DC40RB	DC40RC	DC40WA
BL1815N 1.5Ah	15 min	30 min		BL4020 2.0Ah	22 min	30 min	110 min
BL1820B 2.0Ah	24 min	45 min		BL4025 2.5Ah	28 min	38 min	130 min
BL1830B 3.0Ah	22 min	60 min		BL4040 4.0Ah	45 min	67 min	210 min
BL1840B 4.0Ah	36 min	90 min		BL4050F 5.0Ah	50 min	85 min	260 min
BL1850B 5.0Ah	45 min	110 min		BL4080F 8.0Ah	76 min	170 min	420 min
BL1860B 6.0Ah	55 min	130 min					

Not covered by EPTA-Procedure
Items of standard equipment and specifications may vary by country or area.

Cordless Area Worklight

ML010G 40V^{max}, 18V, 14.4V / AC

Illuminance (High / Med. / Low)	at 1 m from the light source: 550 / 300 / 150 lx
Luminous flux	High / Med. / Low: 5,500 / 3,000 / 1,500 lm
Continuous run time on full battery charge	High / Med. / Low, w/ BL1860B x2: 4.5 / 8.5 / 16 hours High / Med. / Low, w/ BL4040 x2: 6.5 / 11 / 21 hours High / Med. / Low, w/ BL4050F x2: 8.5 / 14 / 27 hours High / Med. / Low, w/ BL4040 x2 & BL1860B x2: 11 / 19.5 / 37 hours High / Med. / Low, w/ BL4050F x2 & BL1860B x2: 13 / 22.5 / 43 hours High / Med. / Low, w/ BL4080F x2: 13 / 23 / 43 hours
Dimensions (L x W x H)	490 x 490 x 814 mm (19-1/4 x 19-1/4 x 32")
Net weight	14.4 - 19.2 kg (31.7 - 42.3 lbs.)
Power supply cord	2.5 m (8.2 ft)

Standard Equipment : AC power cord, Earth grounding plug
Battery & Charger Sold Separately

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202306