





Delivers strong and consistent power for your pruning and wood-cutting tasks



Work efficiency

U % UP*

Battery: BL4025 on a full battery charge

Test conditions

Cut ø50 cypress wood under an optimal pressing load of 25N or less on the cutting edge







Excellent combination of high power and lightweight design Compact yet delivers strong and consistent power



Automatic chain lubrication



minimizes the chance that saw chain will stall due to forgetting to supply chain oil.

Tool-less change and tension adjustment of saw chain



- Simply loosen and re-tighten the lever to automatically adjust the tension of saw chain.
- This easy-to-operate large lever is designed to be pulled up and turned easily.

eXtreme Protection Technology



High water-resistance allows the user to operate the tool even if it is wet with water.

Optional accessory

A hook with quick attachment / detachment

A hook allowing the tool to be attached and detached with one hand to a carabiner or similar.

Part No. 1914Y8-5 For UC029G only





Cordless Pruning Saw Lineup







(RAN) Brake

Automatic Oiling

Chain speed (at no load) Saw chain

Chain oil tank volume Dimensions (L x W x H)

Net weight

DUC150

8.0 m/s Type: 80TXL / Pitch: 0.325" / Gauge: 1.1 mm (0.043") Guide bar length: 150 mm (6") 55 ml (1 9 oz)

w/BL1830B/BL1840B/BL1850B/BL1860B: 459 x 90 x 249 mm (18 x 3-1/2 x 9-3/4") 1.7-2.0 kg (3.7-4.4 lbs.)

DUC101 8.0 m/s

Type: 80TXL / Pitch: 0.325" / Gauge: 1.1 mm (0.043") Guide bar length: 100 mm (4") 55 ml (190z)

w/BL1830B/BL1840B/BL1850B/BL1860B: 408 x 90 x 249 mm (16 x 3-1/2 x 9-3/4") 1.6-2.0 kg (3.5-4.4 lbs.)

UC100D

8.0 m/s Type: 80TXL / Pitch: 0.325" / Gauge: 1.1 mm (0.043") Guide bar length: 100 mm (4")

w/BL1016/BL1021B: 383 x 90 x 220 mm (15-1/8 x 3-1/2 x 8-5/8") 1.5-1.6 kg (3.3-3.5 lbs.)

Accessories

Guide bar 6 set

Part No. 1912F1-4

For saw chain type: 80TXL Length: 150 mm (6") Gauge: 1.1 mm (0.043)



Saw chain 6 set

Part No. 1912E8-3

Type: 80TXL Length: 150 mm (6") Gauge: 1.1 mm (0.043)



Guide bar case 175

Part No. 413T67-3



Holster set

Part No. 1913K4-9

For storing and carrying the tool





File holder set

Part No. D-70948



Sprocket 7 set

Part No. 1911W5-9



Oil vessel set

Part No. 199897-3

100mL



Net weight

(Battery) (Attachment)

Hook complete set

Part No. 1914Y8-5 For UC029G only

A hook allowing the tool to be attached and detached with one hand to a carabiner or similar.





Charging Time

40 V rains	Fast Charging DC40RA	DC40RC
BL4020 2.0Ah	22 min	30 min
BL4025 2.5Ah	28 min	38 min
BL4040/F 4.0Ah	45 min	67 min

Cordless Pruning Saw

UC029G 150 mm (6")

(ERAKE) Brake Constant Speed

Automatic Oiling Anti-restart function

Toolless blade change

Chain speed (at no load) Saw chain Oil tank capacity Vibration level (EN62841-4-1) Vibration K factor (EN62841-4-1) Sound pressure level (EN62841-4-1) Sound power level (EN62841-4-1) Noise K factor (EN62841-4-1) Dimensions (L x W x H) (Battery) (Attachment)

8.0 m/s Type: 80TXL / Pitch: 0.325" / Gauge: 1.1 mm (0.043") Guide bar length: 150 mm (6") 55 mL (1.9 oz) Cutting wood: 4.6 m/s²

Cutting wood: 1.5 m/s² 81 dB(A) 89 dB(A) 3 dB(A) 474 x 95 x 255 mm (18-5/8 x 3-3/4 x 10") Guide bar, Saw chain 2.1 - 2.4 kg (4.6 - 5.3 lbs.) BL4020 - BL4040

Guide bar, Saw Chain, Chain oil

Standard Equipment: Guide bar case, Oil vessel set, Guide bar, Saw chain, Battery, Charger,

The weight may differ depending on the attachment(s), including the battery cartridge. Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan