



# Compact and lightweight, easy to maneuver





Blower

High / Med. / Low:

20/60/120 min



19 min

Battery: BL4025 on a full battery charge







job sites









The garden nozzle is an optional accessory depending on the country.

The air volume has been enhanced by enlarging the suction inlet.



3-stage air volume settings by dial with variable speed control by trigger



**Vacuum function** 

Vacuuming is available with the dust bag\*





\*The dust bag is an optional accessory depending on the country.

# Accessories

## Long nozzle assembly

Part No. 123246-2



# Garden nozzle assembly set

Part No. 191G09-6



# Flexible hose set



#### Flexible hose set





#### **Dust bag assembly**

Part No. 123241-2





#### Brush nozzle set

Part No. 191M30-1





#### Wiper nozzle set

Part No. 191M32-7





#### Tapered nozzle set

Part No. 192236-6



# Charging Time

40 Vision max	Fast Charging  DC40RA	DC40RC
*1 <b>BL4020</b> 2.0Ah	22 min	30 min
*1 <b>BL4025</b> 2.5Ah	28 min	38 min
*1 <b>BL4040/F</b> 4.0Ah	45 min	67 min
<b>BL4050F</b> 5.0Ah	50 min	85 min
<b>BL4080F</b> 8.0Ah	76 min	170 min

<sup>\*1</sup> Recommended battery

# **Cordless Blower**

## **UB002G**

Variable Speed Electronic 3-Speed Standard Equipment: Nozzle assembly, Garden nozzle assembly, Dust bag, Battery, Charger \* EN 62841-1 (Battery)

Blowing force Max air volume Max air velocity Max sealed suction Continuous use (Battery) Vibration level\* Vibration K Factor<sup>3</sup> Sound pressure level\* Sound power level\* Noise K factor\* Dimensions (L x W x H) (Attachment) Net weight

(Battery)

Standard nozzle: 3.1 - 3.2 N / Garden nozzle: 3.0 - 3.1 N Blower: 3.5 - 3.6 m³/min / Vacuum: 2.0 m³/min Standard nozzle: 98 - 99 m/s / Garden nozzle: 75 - 76 m/s 5.4 kPa Blower, High / Med. / Low: 20 / 60 / 120 min. / Vacuum: 19 min. BL4025

Standard nozzle, operation without load (blowing / vacuuming): 2.5 m/s<sup>2</sup> or less Standard nozzle, operation without load (blowing) vacuuming): 1.5 m/s<sup>2</sup>
Standard nozzle, operation without load (blowing): 84 dB(A) / (vacuuming): 87 dB(A)
Standard nozzle, operation without load (blowing): 92 dB(A) / (vacuuming): 95 dB(A)
Standard nozzle, operation without load (blowing): 92 dB(A) / (vacuuming): 95 dB(A)

515 x 156 x 227 mm (20-1/4 x 6-1/8 x 8-15/16")

Standard nozzle 2.0 - 3.5 kg (4.4 - 7.7 lbs.) BL4020 - BL4080F

The weight may differ depending on the attachment(s), including the battery cartridge. Items of standard equipment and specifications may vary by country or area.

# Makita Corporation

