







The tool head is capable of rotating 360 degrees.



Release knob

To retract the ram manually, press the release knob.



LED job light

Single LED with afterglow function



Straps of

Straps on the tool for attaching the optional shoulder strap





Trigger-lock function to minimize accidental pulling of the switch trigger

Soft grip provides increased comfort during use



DTC301 with dies (U-type)

Crimping capacity

Cu Ø19.5 mm (300mm²)

Ø19.5 mm (300mm²)



DTC302 with dies (U-type)

Crimping capacity

Ø22.5 mm (400mm²)

AI Ø19.5 mm (300mm²)



DTC303 without dies

Crimping capacity

Ø17.5 mm (240_{mm²})

AI Ø17.5 mm (240_{mm²})



Accessories

Shoulder belt

Part No. 161347-8



Charging Time

18V DITHIUMHON	DC18RC	DC18SD
BL1815N 1.5Ah	15 min	30 min
BL1820B 2.0Ah	24 _{min}	45 min
BL1830B 3.0Ah	22 min	60 min
BL1840B 4.0Ah	36 min	90 min
BL1850B 5.0Ah	45 min	110 min
BL1860B 6.0Ah	55 min	130 min

Cordless Crimper

DTC303

ED Built-in Job Light
Carrying Case

Output force	60 kN
Crimping capacity	Cu: ø17.5 mm (240 mm²)
	Al: ø17.5 mm (240 mm²)
Dimensions (L x W x H)	401 x 82 x 348 mm
	(15-3/4 x 3-1/4 x 13-3/4")
(Battery)	BL1860B
Net weight	5.3 - 5.7 kg (11.7 - 12.6 lbs.)
(Battery)	BL1815N - BL1860B

Standard Equipment : Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combinations are shown in the table.

Items of standard equipment and specifications may vary by country or area.

Makita Corporation



