



Cordless Narrow Crown Stapler DST630

Satisfy Professional's Needs



Offers a similar feel to using a
pneumatic stapler with excellent
rapid firing capability



Nail capacity

Type: **18 Ga**
narrow crown staples

Length: **9.5 - 38 mm**

Rapid firing capability

5.8 shots per sec.
[with BL1820B]

Work amount

1,800 staples
[with BL1820B]

With a lightweight design and optimal balance, it reliably drives staples into hard woods and materials

Rapid firing capability

Incorporating a pneumatic spring structure and driven by a BL motor, superior rapid firing capability has been achieved compared with competitors' models.

**BL
MOTOR**



**18V
LITHIUM-ION**

Belt hook

Can be attached on either the left or right side

LED job light

Single LED with preglow and afterglow functions



Main power switch

Magazine capacity

100 staples (one strip)
(Maximum: 110)

Slim nose

With an easy-to-aim ejection section for better visibility when driving staples

Window for checking remaining nail quantity



XPT

**eXtreme Protection
Technology**

Tool-less nail jam clearing

Staples can be removed without tools in case of jamming

Anti-dry fire mechanism

When the remaining staples reach 5 to 7, the tool automatically stops to avoid dry firing.



Driving depth adjustment with the dial



Operation mode selection

Selectable from Full sequential actuation mode (for single nailing) / Contact actuation mode (for continuous nailing)



Charging Time

| | Fast Charging | | |
|----------------------|---------------|----------------|--|
| | DC18RC | DC18SD | |
| BL1815N 1.5Ah | 15 min | 30 min | |
| BL1820B 2.0Ah | 24 min | 45 min | |
| BL1830B 3.0Ah | 22 min | 60 min | |
| BL1840B 4.0Ah | 36 min | 90 min | |
| BL1850B 5.0Ah | 45 min | 110 min | |
| BL1860B 6.0Ah | 55 min | 130 min | |

Cordless Narrow Crown Stapler

DST630

- Anti-restart function
- Depth Adjustment
- Sequential and Bump-fire
- Auto Firing Stop
- Built-in Job Light
- Carrying Case

| | |
|--|--|
| Nail capacity | Gauge: 18 Ga Length: 9.5 - 38 mm (3/8 - 1-1/2") Outer width: 5.7 - 6.35 mm (7/32 - 1/4") |
| Magazine capacity | 110 staples |
| Approx. work volume on a full battery charge (Battery) | 1,800 shots (BL1820B) |
| Vibration level (EN60745-2-16) | 2.5 m/s ² or less |
| Vibration K factor (EN60745-2-16) | 1.5 m/s ² |
| Sound pressure level (EN60745-2-16) | 79 dB(A) |
| Noise K factor (EN60745-2-16) | 3 dB(A) |
| Dimensions (L x W x H) (Battery) | 246 x 96 x 282 mm (9-11/16 x 3-3/4 x 11-1/8") |
| Net weight (Battery) | BL1820B 2.8 - 3.1 kg (6.2 - 6.8 lbs.) BL1815N - BL1860B |

Standard Equipment : Nose adapter, Hook, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.
Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan



PRINTED IN JAPAN 202503

www.makita.com