



# Cordless Brad Nailer DBN501



# 18Ga Brad Nailer



Brad Nail Capacity

Length: **15 - 50 mm**

Rapid firing capability

**5.4** shots per second



# Offers a similar feel to using a pneumatic nailer and excellent maneuverability

## Rapid firing capability

Incorporating a pneumatic spring structure and driven by a BL motor, superior rapid firing capability has been achieved compared to competitors' models.



**BL MOTOR**

## Bumper

Protects workpieces from scratches or damage.



## Belt hook

Convenient for temporarily hanging the tool

## LED job light



## Main power switch

## Indicator

Indicates remaining nail capacity



## Slim nose

With an easy-to-aim ejection section for better visibility when driving nails

## Window for checking remaining nail quantity

The magazine features a transparent part, enabling the quantity of remaining nails to be checked.



**extreme Protection Technology**

## Tool-less nail jam clearing

Nails can be removed without tools in case of jamming



## Anti-dry fire mechanism

Avoids dry firing by locking the contact arm when the remaining nails are 5 to 7.

## Driving depth adjustment

For a wide variety of finish applications



## Operation mode

Selectable from Full sequential actuation mode (for single nailing) / Contact actuation mode (for continuous nailing)



## Accessories

### Brad nail

5,000pcs/box

Length	Part No.
15mm (5/8")	F-31867
20mm (3/4")	F-31870
25mm (1")	F-31883
30mm (1-3/16")	F-31896
32mm (1-1/4")	F-31902
35mm (1-3/8")	F-31915
38mm (1-1/2")	F-31928
40mm (1-9/16")	F-31931
45mm (1-3/4")	F-31944
50mm (2")	F-31957

## Charging Time

		Fast Charging	
		DC18RC	DC18SD
	<b>BL1815N</b> 1.5Ah	<b>15 min</b>	<b>30 min</b>
	<b>BL1820B</b> 2.0Ah	<b>24 min</b>	<b>45 min</b>
	<b>BL1830B</b> 3.0Ah	<b>22 min</b>	<b>60 min</b>
	<b>BL1840B</b> 4.0Ah	<b>36 min</b>	<b>90 min</b>
	<b>BL1850B</b> 5.0Ah	<b>45 min</b>	<b>110 min</b>
	<b>BL1860B</b> 6.0Ah	<b>55 min</b>	<b>130 min</b>

## Cordless Brad Nailer

### DBN501

	Anti-restart function	Nail capacity	Length: 15 - 50 mm (9/16 - 2") Gauge: 18 Ga
	Depth Adjustment	Magazine capacity	110 nails
	Sequential and Bump-fire	Shot q'ty on a single full battery charge (Battery)	1,700 pcs
	Auto Firing Stop	Vibration level (EN60745-2-16)	2.5 m/s <sup>2</sup> or less
	Built-in Job Light	Vibration K factor (EN60745-2-16)	1.5 m/s <sup>2</sup>
	Carrying Case	Sound pressure level (EN60745-2-16)	82 dB(A)
		Sound power level (EN60745-2-16)	93 dB(A)
		Noise K factor (EN60745-2-16)	3 dB(A)
		Dimensions (L x W x H)	246 x 96 x 301 mm (9-11/16 x 3-3/4 x 11-7/8")
		(Battery)	BL1820B
		Net weight (Battery)	2.7 - 3.0 kg (6.0 - 6.6 lbs.)
		(Battery)	BL1815N - BL1860B

#### Standard Equipment :

Nose adapter, Battery, Charger, Hook

The weight may differ depending on the attachment(s), including the battery cartridge.  
Items of standard equipment and specifications may vary by country or area.

# Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

