



Cordless Framing Nailer BN001G / BN002G



40V Li-ion
max



photo:BN001G

**Excellent rapid-fire performance
with a pneumatic feel**

Rapid firing capability

about 4 shots per second

BN001G

Clipped-head



Nail capacity

Length

50-90 mm

Gauge

2.9-3.3 mm

Collation angle display

30-34°



BN002G

Round-head



Nail capacity

Length

50-90 mm

Gauge

2.9-3.8 mm

Collation angle display

21°



photo: BN001G



photo: BN002G



photo: BN002G



■ Accessories

Nose Adapter Set

For driving nails above the surface
for easier removal
from formwork.

Part No. 1916P4-2



Extended Capacity Magazine Set

Holds more nails for
fewer reloads and
better efficiency.



BN001G:

Part No. 1917P3-0

Maximum magazine
capacity: 97 nails



BN002G:

Part No. 1914P9-0

Maximum magazine
capacity: 78 nails

■ Charging Time

	Fast Charging	DC40RA	DC40RC
*1 BL4020 2.0Ah	22 min	30 min	
*1 BL4025 2.5Ah	28 min	38 min	
*1 BL4040/F 4.0Ah	45 min	67 min	
BL4050F 5.0Ah	50 min	85 min	
BL4080F/H 8.0Ah	76 min	170 min	

*1 Recommended battery

Cordless Framing Nailer

BN001G / BN002G

	BN001G	BN002G
Anti-restart function	Nail capacity	Length: 50 - 90mm (2 - 3-1/2")
Depth Adjustment	Length: 50 - 90mm (2 - 3-1/2")	Gauge: 2.9 - 3.3mm (0.113 - 0.131")
Sequential and Bump-fire	Rapid firing capability per second (Battery)	Collation angle display: 30 - 34°
Auto Firing Stop	Work volume on a full battery charge (Battery)	Max magazine capacity 58 nails
Built-in Job Light	Rapid firing capability per second (Battery)	1,020 (BL4025)
Carrying Case	Vibration level	4 (BL4025)
	Uncertainty (K) for Vibration	3.6 m/s ² (EN60745-2-16)
	Sound pressure level	1.5 m/s ² (EN60745-2-16)
	Sound power level	90 dB (A) (EN60745-2-16)
	Uncertainty (K) for Noise	101 dB (A) (EN60745-2-16)
	Dimensions (L x W x H)	101 dB (A) (EN60745-2-16)
	(Battery)	3 dB (A) (EN60745-2-16)
	Net weight	3 dB (A) (EN60745-2-16)
	(Battery)	326 x 186 x 358 mm (12-7/8 x 7-3/8 x 14-1/8")
		389 x 189 x 358 mm (15-1/4 x 7-7/16 x 14-1/8")
		BL4025
		BL4020
		BL4020-BL4080F
		BL4020 - BL4080F

Standard Equipment : Hex wrench, Hook, Rafter hook, Nose adapter, Battery, Charger

The net weight value includes the lightest and heaviest combination of the attachment(s) and battery cartridge(s) which are specified in the instruction manual.

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202510



www.makita.com