



Cordless Finish Nailer DBN620



Excellent maneuverability with a pneumatic-like trigger responsiveness




Finish Nail Capacity
Length: 32 - 64 mm



Excellent rapid-fire performance and power with cordless convenience

Rapid-fire performance

Powered by brushless motor and pneumatic spring mechanism



**BL
MOTOR**

Bumper

Protects workpieces from scratches or damage.



Main power switch

Belt hook

Convenient for temporarily hanging the tool

LED job light



Anti-dry fire mechanism

Avoids dry firing by locking the contact arm when the remaining nails are 4 to 6.

Slim nose

With an easy-to-aim ejection section for better visibility when driving nails

Tool-less jammed nail clearing

Nails can be removed without tools in case of jamming



Driving depth adjustment

For a wide variety of finish applications



Window for checking remaining nail quantity

The remaining nails can be checked.



eXtreme Protection Technology

Operation mode

Selectable from Full sequential actuation mode (for single nailing) / Contact actuation mode (for continuous nailing)



Accessories

Finish nail

15Ga
Finish Nail
(4,000 pcs/box)

Length	Part No.
32mm (1-1/4")	F-31960
38mm (1-1/2")	F-31973
45mm (1-3/4")	F-31986
50mm (2")	F-31999
57mm (2-1/4")	F-32007
64mm (2-1/2")	F-32010

Charging Time

Battery	Fast Charging	
	DC18RC	DC18SD
BL1815N 1.5Ah	15 min	30 min
BL1820B 2.0Ah	24 min	45 min
BL1830B 3.0Ah	22 min	60 min
BL1840B 4.0Ah	36 min	90 min
BL1850B 5.0Ah	45 min	110 min
BL1860B 6.0Ah	55 min	130 min
BLB182 2.0Ah	90 min	

Compatible with charger DCB18WA only

Cordless Finish Nailer

DBN620

Anti-restart function	Nail capacity	Length: 32 - 64 mm (1-1/4 - 2-1/2") Gauge: 15 Ga
Depth Adjustment	Capacity	Max magazine capacity: 108 nails Collation angle display: 34°
Sequential and Bump-fire	Shot q'ty on a single full battery charge (Battery)	800 pcs BL1820B
Auto Firing Stop	Rapid firing capability per second (Battery)	3.2 BL1820B
Built-in Job Light	Vibration level	2.7m/s ² (EN60745-2-16)
Carrying Case	Uncertainty (K) for Vibration	1.5m/s ² (EN60745-2-16)
	Sound pressure level	86dB(A) (EN60745-2-16)
	Sound power level	97dB(A) (EN60745-2-16)
	Uncertainty (K) for Noise	3dB(A) (EN60745-2-16)
	Dimensions (L x W x H)	297 x 142 x 338 mm (11-3/4 x 5-5/8 x 13-1/4")
	Net weight (Battery)	3.1 kg (6.8 lbs.) BL1820B

Standard Equipment:
Nose adapter, Hook, Battery, Charger

The net weight value includes the lightest and heaviest combination of the attachment(s) for normal and safe use and battery cartridge(s) which are specified in the instruction manual.
Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

