



**Cordless Job Site Speaker
DMR200**



Portable Job Site Speaker with Bluetooth connection



Powered by AC or DC :

AC via AC adapter

DC via 10.8V, 14.4V, 18V Li-ion battery

Enjoy high quality sound from 2-way speaker with 101.6mm woofer and 36mm tweeter.



Storage compartment for mobile device

Mobile device charging is possible while stored.

Note: Mobile phone is not included.



3-color LED indicators Condition of Bluetooth connection



← Aux in indicator

Bluetooth connection states

↑ Volume max. or min. indicator/
Low battery indicator

IP64-rated dust and shower-proof construction

For use in outdoor applications or harsh environments 3

Power source

Li-ion battery (slide type)

10.8V



14.4V
18V



CXT

LXT


AC



USB output port allows for charging.



Connection port



AC adapter



Can be connected to external audio source with a commercial connecting cable.

Continuous run time on a single full battery charge

| Voltage | CXT | | | 14.4V LITHIUM-ION | | | | | 18V LITHIUM-ION | | | | | |
|-----------------------|-----------------|------------------|------------------|-------------------|------------------|-----------------|-----------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|
| | BL1015 1.5Ah | BL1020B 2.0Ah | BL1040B 4.0Ah | BL1415N 1.5Ah | BL1430B 3.0Ah | BL1440 4.0Ah | BL1450 5.0Ah | BL1460B 6.0Ah | BL1815N 1.5Ah | BL1820B 2.0Ah | BL1830B 3.0Ah | BL1840B 4.0Ah | BL1850B 5.0Ah | BL1860B 6.0Ah |
| AUX IN | 12 | 15 | 31 | 10 | 16 | 26 | 31 | 34 | 9.5 | 13 | 18 | 25 | 32 | 39 |
| Bluetooth | 11 | 14 | 28 | 9.0 | 15 | 24 | 29 | 32 | 9.0 | 12 | 17 | 24 | 31 | 37 |
| AUX IN + USB(2.1A) | 1.0 | 1.0 | 2.5 | 1.0 | 2.0 | 3.0 | 3.5 | 4.0 | 1.5 | 2.0 | 3.0 | 4.0 | 5.5 | 6.5 |
| Bluetooth + USB(2.1A) | 1.0 | 1.0 | 2.5 | 1.0 | 2.0 | 3.0 | 3.5 | 4.0 | 1.5 | 2.0 | 3.0 | 4.0 | 5.5 | 6.5 |

Cordless Job Site Speaker

DMR200 10.8-18V / AC

Dimensions (with carry handle in upright position).
Battery and charger are sold separately.

Standard Equipment : AC power adapter

Bluetooth

Version 4.0
Profile A2DP / SCMS-T / AVRCP
Supported Codec SBC
Max Transmission Range 10 m (33 ft)

Practical max output

18V: 10W/ 10.8V: 3.5 W
Speaker size Woofer: Ø101.6mm, Tweeter: Ø36mm
Dimensions 211x203x199mm (8-5/16"x8"x7-7/8")
(L x W x H)
Net weight 2.9 kg (6.4 lbs)(BL1015)
3.3kg (7.2lbs)(BL1850B)

weight according to EPTA-Procedure 01/ver.2.1
Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201607