

Satisfy Professional's Needs



# Cordless Screwdriver DFS250 / DFS251



for Decking applications (DFS250)



for Self drilling screw applications (DFS251)

## 2,500 RPM High Torque Push Drive Technology Screwdriver

# DFS250 : suitable for decking applications

# DFS251: suitable for self drilling screw applications



- Maintenance-free due to no brush
- Energy production is more efficient than brushed DC motor because of no friction loss caused by brushes, enabling to lower amperage for reduced heat production and increased work amount on a single full battery charge.

### Best possible tool body for screwdriving

- ergonomically designed to:
- minimize hand fatigue and pain even in long continuous operation.
  - give maximum power thrust.
  - allow for much smoother and easier trigger pull.
  - provide comfortable grip and better control with enlarged non-slip elastomer.

### Lock-on button for continuous screwdriving

### Powered by 18V Li-ion batteries



with Battery fuel gauge

- BL1860B: 18V 6.0Ah
- BL1850B: 18V 5.0Ah
- BL1840B: 18V 4.0Ah
- BL1830B: 18V 3.0Ah
- BL1820B: 18V 2.0Ah
- \*BL1815N: 18V 1.5Ah
- \*without Battery fuel gauge



### Single LED job light with afterglow function

- convenient for operation in dark job sites
- keeps on illuminating about 12-13 seconds after trigger release.



Photo : DFS250

## Push Drive Technology

- In lock-on mode, the motor does not rotate under no load to minimize power consumption, and starts rotating at full speed only when screws are inserted into a board.
- With ON/OFF switch



Photo : DFS251

### Charger

Fast Charger  
DC18RC



Two Port Multi  
DC18RD



Charging time (3.0Ah)  
22minutes

Four Port Multi  
DC18SF



DC18SD



DC18SE  
(Automotive)



## Cordless Screwdriver DFS250 / DFS251

- Variable Speed
- Reversing
- Built-in Job Light
- Carrying Case

### Standard Equipment :

DFS250: Phillips Bit, Magnetic Bit Holder, Belt Clip, Battery, Charger

DFS251: Magnetic Socket Bit, Battery, Charger

	DFS250	DFS251
<b>Capacity</b>	Coarse Thread: 4.5 x 90 mm (3/16" x 3-1/2") Self-Drilling Screw: 6 mm (1/4") Drywall Screw: 5 mm (3/16")	Self-Drilling Screw: 6 mm (1/4") Drywall Screw: 5 mm (3/16") Hex Socket Screw: 6 mm (1/4")
<b>Driving Shank (Hex)</b>	6.35 mm (1/4")	6.35 mm (1/4")
<b>No Load Speed (RPM)</b>	0 - 2,500	0 - 2,500
<b>Vibration Level</b>	Screwdriving without Impact: 2.5 m/s <sup>2</sup> or less	Screwdriving without Impact: 2.5 m/s <sup>2</sup> or less
<b>Sound Pressure Level</b>	72 dB(A)	72 dB(A)
<b>Sound Power Level</b>	N/A dB(A)	N/A dB(A)
<b>Dimensions (L x W x H)</b>	259x79x259mm (10-1/4"x3-1/8"x10-1/4")	237x79x259mm (9-3/8"x3-1/8"x11-1/4")
<b>Net weight</b>	BL1815N: 1.6 kg (3.5 lbs.) BL1860B: 1.8 kg (4.1 lbs.)	BL1815N: 1.5 kg (3.3 lbs.) BL1860B: 1.8 kg (3.9 lbs.)

weight according to EPTA-Procedure 01/ver.2.1

Items of standard equipment and specifications may vary by country or area.

## Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 2017/01