



Angle Grinder  
GA9060 Series

# HEAVY DUTY GRINDER



GA7061/R, GA7063/R, GA9061/R, GA9063/R

Continuous Rating Input

**2,200W**

**180mm (7")**

GA7060/R, GA7061/R  
GA7064

**230mm (9")**

GA9060/R  
GA9061/R



GA7062/R  
GA7063/R



GA9062/R  
GA9063/R

# More durable for heavy

GA7060/R  
GA7061/R  
GA7064  
GA9060/R  
GA9061/R

Compact body size  
Over length **450mm**  
23mm More compact body size  
than the predecessor model



Photo: GA9061R

GA7062/R  
GA7063/R  
GA9062/R  
GA9063/R



Photo: GA9062R


**D-shape Handle**  
protects user's hand from materials.



(GA7061/R, GA9061/R, GA7063/R, GA9063/R)  
provides increased machine durability by  
absorbing the vibration produced by the  
wheel grinding or cutting material.

# Heavy duty applications

## Rigid motor housing




## Newly designed brush holder




Change from basic spring to Spiral spring without losing the compact body yet extending the service life of Carbon brush.

## Anti layer short Armature



The fixing strength of coil has been significantly improved by adding cotton sleeve and felt sheet.

## Switch cover and Sponge sheet



prevents entering of metal particles to Switch terminals to improve the protection against a short circuit.

## Newly designed Shaft lock



enables to press the button from a slant angle, for easy handing even with protection gloves.

## Anti-restart function

(GA7060R, GA9061R, GA7062R, GA7063R, GA9060R, GA9061R, GA9062R, GA9063R)



- Prevents accidental start-up even if the tool is plugged to power source with the switch "ON".
- Blinking red LED at the rear cover warns that Anti-restart function has been activated.

## Soft start

(GA7060R, GA9061R, GA7062R, GA7063R, GA9060R, GA9061R, GA9062R, GA9063R)

minimizes start-up shock, and makes the tool start smoothly.

## Product Comparison List

Model No.	Net weight	Handle	No Load Speed (RPM)	 SJS II	Anti-restart function	 Soft start
180mm (7")	GA7060	5.3kg (11.7lbs)	8,500			
	GA7060R	5.4kg (11.9lbs)	8,500		✓	✓
	GA7061	5.5kg (12.1lbs)	8,500	✓		
	GA7061R	5.5kg (12.1lbs)	8,500	✓	✓	✓
	GA7062	5.4kg (11.9lbs)	D-shape	8,500		
	GA7062R	5.5kg (12.1lbs)	D-shape	8,500		✓
	GA7063	5.6kg (12.4lbs)	D-shape	8,500	✓	
	GA7063R	5.6kg (12.4lbs)	D-shape	8,500	✓	✓
	GA7064	5.3kg (11.7lbs)		6,600		
230mm (9")	GA9060	5.5kg (12.1lbs)	6,600			
	GA9060R	5.6kg (12.4lbs)	6,600		✓	✓
	GA9061	5.7kg (12.6lbs)	6,600	✓		
	GA9061R	5.7kg (12.6lbs)	6,600	✓	✓	✓
	GA9062	5.6kg (12.4lbs)	D-shape	6,600		
	GA9062R	5.7kg (12.6lbs)	D-shape	6,600		✓
	GA9063	5.8kg (12.8lbs)	D-shape	6,600	✓	
	GA9063R	5.8kg (12.8lbs)	D-shape	6,600	✓	✓

## Accessories





**Anti Vibration**  
AVT Grip Part No. 194290-6







**Dust Collecting Wheel Guard** Part No. 194044-1



### Angle Grinder GA7060/R, GA7061/R, GA7062/R, GA7063/R, GA7064 180mm (7") 218 mm

	GA7060 / GA7060R	GA7061 / GA7061R	GA7062 / GA7062R	GA7063 / GA7063R	GA7064
 Double Insulation	2,200W	2,200W	2,200W	2,200W	2,200W
 Soft Start (GA7060R, GA7061R, GA7062R, GA7063R)	180 mm (7")	180 mm (7")	180 mm (7")	180 mm (7")	180 mm (7")
 Dust Collection	8,500	8,500	8,500	8,500	6,600
 SUPER JOINT SYSTEM	7.5 m/s <sup>2</sup>	6.5 m/s <sup>2</sup>	7.5 m/s <sup>2</sup>	6.5 m/s <sup>2</sup>	4.5 m/s <sup>2</sup>
	91 dB(A)	91 dB(A)	91 dB(A)	91 dB(A)	91 dB(A)
	102 dB(A)	102 dB(A)	102 dB(A)	102 dB(A)	102 dB(A)
	450x200x144mm	450x200x145mm	450x200x144mm	450x200x145mm	450x200x144mm
	(17-3/4"x7-7/8"x5-5/8")	(17-3/4"x7-7/8"x5-3/4")	(17-3/4"x7-7/8"x5-5/8")	(17-3/4"x7-7/8"x5-3/4")	(17-3/4"x7-7/8"x5-7/8")
	GA7060: 5.3 kg (11.7 lbs)	5.5 kg (12.1 lbs)	GA7062: 5.4 kg (11.9 lbs)	5.6 kg (12.4 lbs.)	5.3 kg (11.7 lbs.)
	GA7060R: 5.4kg (11.9lbs)		GA7062R: 5.5kg (12.1lbs)		
	2.5 m (8.2 ft)	2.5 m (8.2 ft)	2.5 m (8.2 ft.)	2.5 m (8.2 ft.)	2.5 m (8.2 ft.)
	<b>Standard Equipment</b> : Side grip, Lock nut wrench (Tool does not come with depressed center wheel.)				

### Angle Grinder GA9060/R, GA9061/R, GA9062/R, GA9063/R 230mm (9") 218 mm

	GA9060 / GA9060R	GA9061 / GA9061R	GA9062 / GA9062R	GA9063 / GA9063R
 Double Insulation	2,200W	2,200W	2,200W	2,200W
 Soft Start (GA9060R, GA9061R, GA9062R, GA9063R)	230 mm (9")	230 mm (9")	230 mm (9")	230 mm (9")
 Dust Collection	6,600	6,600	6,600	6,600
 SUPER JOINT SYSTEM	6.0 m/s <sup>2</sup>	5.5 m/s <sup>2</sup>	6.0 m/s <sup>2</sup>	5.5 m/s <sup>2</sup>
	91 dB(A)	91 dB(A)	91 dB(A)	91 dB(A)
	102 dB(A)	102 dB(A)	102 dB(A)	102 dB(A)
	450x250x144mm	450x250x145mm	450x250x144mm	450x250x145mm
	(17-3/4"x9-7/8"x5-5/8")	(17-3/4"x9-7/8"x5-3/4")	(17-3/4"x9-7/8"x5-5/8")	(17-3/4"x9-7/8"x5-3/4")
	GA9060: 5.5 kg (12.1 lbs)	5.7 kg (12.6 lbs)	GA9062: 5.6 kg (12.4 lbs.)	5.8 kg (12.8 lbs.)
	GA9060R: 5.6 kg (12.4lbs)		GA9062R: 5.7 kg (12.6 lbs.)	
	2.5 m (8.2 ft)	2.5 m (8.2 ft)	2.5 m (8.2 ft.)	2.5 m (8.2 ft.)
	<b>Standard Equipment</b> : Side grip, Lock nut wrench (Tool does not come with depressed center wheel.)			

\* Triaxial vector sum. According to EN60745-2-3.

weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

# Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201704