



Cordless Impact Driver TD022D

**Compact and
lightweight for
easy handling**



More work amount

40%UP*

Work amount on a single full battery charge

**with 7.2V -1.5Ah NEW
Li-ion battery BL0715**

*conventional models



Fastening speed 10%UP*

**High fastening torque 25N·m
High no load speed 0-2,450 rpm**



Easily converted from straight to pistol-type impact driver

Compact bit sleeve


Multi-functional rotary type switch

- features variable speed control, enabling precision adjustment of rotational speed for careful screwdriving.
- with reversing function
- easy to turn on/off, adjust rotational speed and reverse rotation.



LED Job light with preglow function

Brightly illuminates a spot and the periphery by enlarging the illuminated area.



Maneuverable



Electric brake



Soft grip

Can be used as a hand Screwdriver



Convenient for :

- driving screws in delicate places where driving with impact mechanism may damage screw or workpiece.
- making sure that screws are securely tightened at proper torque.

Compact (227/ 282mm) and lightweight design (560g)



7.2V -1.5Ah Li-ion battery of stick type as a power source

Use of the stick-type Li-ion battery allows for compact and lightweight tool design.

Chargeable at approx. 35minutes with Charger DC10WA



Battery BL0715



Charger DC10WA



Cordless Impact Driver

TD022D

- Variable Speed
- Brake
- Reversing
- Built-in Job Light
- Carrying Case

Hex Shank	6.35 mm (1/4")
No Load Speed (RPM)	0 - 2,450
Impacts Per Minute (IPM)	0 - 3,000
Max Fastening Torque	25 N·m (220 in·lbs)
Capacity	Machine screw : M3 - M8 (1/8" - 5/16") Standard bolt : M3 - M8 (1/8" - 5/16") High strength bolt : M3 - M6 (1/8" - 1/4") Coarse thread (in length): 22 - 45mm (7/8" - 1-3/4")
Vibration Level	Fastening Bolt: 7.0 m/s ²
Sound Pressure Level	85 dB(A)
Sound Power Level	96 dB(A)
Dimensions (L x W x H)	Straight Type: 282x42x52mm (11-1/8"x1-5/8"x2-1/16") Pistol Type: 227x42x142mm (8-15/16"x1-5/8"x5-5/8")
Net weight	0.56 kg (1.2 lbs)

Standard Equipment : Holster, Bit set, Battery, Charger

weight according to EPTA-Procedure 01/ver.2.1

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201609