



# Petrol Blower

EB5300TH

Tube-mounted throttle

EB5300WH

Hip-mounted throttle



# High power and lightweight

Larger air volume  
**15**  
m<sup>3</sup>/min

Max air velocity  
**98**  
m/s

**Tube-mounted throttle**  
EB5300TH

**Hip-mounted throttle**  
EB5300WH



# New 52.5 mL 4-stroke engine



## MM4



### Low vibration for reduced operator stress and fatigue

- Vibration to the back of operator is reduced by the 4 damper springs mounted between the engine and the backpack frame.
- Vibration at the handle is significantly reduced by effectively damping transmission of vibration from the engine to the nozzle.



### Comfortable backpack harness

- Cushioned back padding and shoulder straps are well-ventilated for effective sweat evaporation.
- Adjustable straps provide a perfect fit for every user.



Larger air volume

**15**  
m<sup>3</sup>/min

Max air velocity

**98**  
m/s



### Improved by 20% in air flow efficiency

Fan shape has been changed. Air can be pushed out smoothly with less air flow loss. (compared with our current Fan)



### Easy-to-pull recoil starter

### Accessories

**Oil bottle set**  
220ml 10W-30  
Part No. 198279-6



**Hip belt set**

Part No. 198645-7



**Flat nozzle**

Part No. 196911-6



**Band 25 set**

Part No. 196733-4



**End nozzle 90-62**

Part No. 198034-6



**Long pipe 90 set**

Part No. 197723-0



**Short pipe 90 set**

Part No. 196912-4



**Engine maintenance kit M**

Part No. 198282-7

**Air cleaner element set M**

Part No. 198284-3

### Petrol Blower

**EB5300TH** Tube-mounted throttle / **EB5300WH** Hip-mounted throttle

	EB5300TH	EB5300WH
Anti Vibration		
Primer Pump		
Capacitor discharge ignition		
Auto Decompression		
<b>Displacement</b>	52.5 mL	52.5 mL
<b>Max Air Volume</b>	15 m <sup>3</sup> /min (516 CFM)	15 m <sup>3</sup> /min (516 CFM)
<b>Max Air Velocity</b>	98 m/s (220 MPH)	98 m/s (220 MPH)
<b>Fuel Tank Capacity</b>	1.8 L (61 oz.)	1.8 L (61 oz.)
<b>Spark plug</b>	NGK CMR6H	NGK CMR6H
<b>Sound Pressure Level</b>	96.0 dB(A)	96.0 dB(A)
<b>Sound Power Level</b>	102.5 dB(A)	102.5 dB(A)
<b>Vibration Level Right Handle</b>	2.2 m/s <sup>2</sup>	2.3 m/s <sup>2</sup>
<b>Vibration Level Left Handle</b>	-	0.5 m/s <sup>2</sup>
<b>Dimensions (L x W x H)</b>	320x450x475mm (12-5/8"x17-3/4"x18-3/4")	320x510x475mm (17-3/4"x20"x18-3/4")
<b>Net weight</b>	8.9 kg (19.7 lbs.)	9.1 kg (20.1 lbs.)

#### Standard Equipment :

Oil bottle set, Box Wrench, Driver, Flexible Pipe, Swivel Pipe, Hose Clamp, End nozzle, Flat Nozzle, Long Pipe, Short Pipe, Accessory Bag, Cable Holder

Net weight: W/O Fuel & Blower pipe. Overall length: W/O Blower pipe

Items of standard equipment and specifications may vary by country or area. weight according to EPTA-Procedure 01/ver.2.1

## Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201703